



SAFETY DATA SHEET

Rainshield Flat White Pastel

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name Rainshield Flat White Pastel

Product number RS-3360

Recommended use of the chemical and restrictions on use

Application Paint.

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier See Manufacturer

Contact Person Milton Arnold

Manufacturer LANCO & HARRIS CORP.
600 MID FLORIDA DRIVE
ORLANDO, FL. 32824
407-240-4000
www.lancopaints.com

Emergency telephone number

Emergency telephone Office 407-240-4000 9 – 5 eastern M_F
Chemtrec 24 Hours: 800-424-9300

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Carc. 2 - H351

Environmental hazards Aquatic Acute 2 - H401 Aquatic Chronic 2 - H411

Label elements

Pictogram



Signal word Warning

Hazard statements H351 Suspected of causing cancer.
H411 Toxic to aquatic life with long lasting effects.

Rainshield Flat White Pastel

Precautionary statements	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P308+P313 If exposed or concerned: Get medical advice/ attention. P391 Collect spillage. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.
Contains	Titanium dioxide, diuron

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Limestone	10-30%
CAS number: 1317-65-3	
Titanium dioxide	10-30%
CAS number: 13463-67-7	
Silicon dioxide	<1%
CAS number: 7631-86-9	
diuron	<1%
CAS number: 330-54-1	
M factor (Acute) = 10	M factor (Chronic) = 10
Aluminum hydroxide	<1%
CAS number: 21645-51-2	
t-Butyl hydroperoxide	<1%
CAS number: 75-91-2	
Zirconium(IV) oxide	<1%
CAS number: 1314-23-4	
3-iodo-2-propynyl butylcarbamate	<1%
CAS number: 55406-53-6	
M factor (Acute) = 10	M factor (Chronic) = 1
octhilinone	<1%
CAS number: 26530-20-1	
M factor (Acute) = 1	M factor (Chronic) = 10

Rainshield Flat White Pastel

Composition comments	* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.
4. First-aid measures	
Description of first aid measures	
General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin Contact	It is important to remove the substance from the skin immediately. In the event of any sensitization symptoms developing, ensure further exposure is avoided. Remove contamination with soap and water or recognized skin cleansing agent. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Rinse with water. Do not rub eye. Remove any contact lenses and open eyelids wide apart. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.
Most important symptoms and effects, both acute and delayed	
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
Ingestion	May cause sensitization or allergic reactions in sensitive individuals. May cause irritation. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
Skin contact	May cause skin sensitization or allergic reactions in sensitive individuals. Redness. Irritating to skin. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
Eye contact	Irritating to eyes.
Indication of immediate medical attention and special treatment needed	
Notes for the doctor	Treat symptomatically. May cause sensitization or allergic reactions in sensitive individuals.
5. Fire-fighting measures	
Extinguishing media	
Suitable extinguishing media	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Special hazards arising from the substance or mixture	
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.
Advice for firefighters	

Rainshield Flat White Pastel

Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Avoid contact with skin and eyes.
-----------------------------	---

Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.
----------------------------------	---

Methods and material for containment and cleaning up

Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. For waste disposal, see Section 13.
--------------------------------	---

Reference to other sections

Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
------------------------------------	---

7. Handling and storage

Precautions for safe handling

Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. May cause cancer. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.
--------------------------	--

Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.
---	--

Conditions for safe storage, including any incompatibilities

Storage precautions	Store locked up. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.
Storage class	Miscellaneous hazardous material storage.

Rainshield Flat White Pastel

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Limestone

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction

Titanium dioxide

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

A4

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Silicon dioxide

Long-term exposure limit (8-hour TWA): OSHA 0.8 mg/m³

diuron

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

A4

Aluminum hydroxide

Long-term exposure limit (8-hour TWA): ACGIH 1 mg/m³ respirable fraction

Zirconium(IV) oxide

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH Threshold Limit Values (TLV) 5 mg/m³

Short-term exposure limit (15-minute): ACGIH 10 mg/m³

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

Titanium dioxide (CAS: 13463-67-7)

Immediate danger to life and health 5000 mg/m³

Silicon dioxide (CAS: 7631-86-9)

Immediate danger to life and health 3000 mg/m³

Exposure controls

Protective equipment



Rainshield Flat White Pastel

Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Hand protection	Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.
Respiratory protection	Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Liquid.
Color	Various colors.
Odor	Mild.
Odor threshold	Not available.
pH	pH (concentrated solution): 8.5 - 9.5
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	Not applicable.
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Lighter than air.
Solubility(ies)	Soluble in water.

Rainshield Flat White Pastel

Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not applicable.
Specific Gravity (H₂O = 1)	1.366
Oxidizing properties	Not available.
Coating v.o.c.	37 g/l
Material v.o.c.	18 g/l

10. Stability and reactivity

Reactivity	There are no known reactivity hazards associated with this product.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
-------------------------------------	--

Acute toxicity - dermal

Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
---------------------------------------	--

ATE dermal (mg/kg)	160,427.81
---------------------------	------------

Acute toxicity - inhalation

Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
---	--

ATE inhalation (dusts/mists mg/l)	26.74
--	-------

Skin corrosion/irritation

Animal data	Irritating.
--------------------	-------------

Serious eye damage/irritation

Serious eye damage/irritation	Causes serious eye irritation.
--------------------------------------	--------------------------------

Respiratory sensitization

Rainshield Flat White Pastel

Respiratory sensitization	Based on available data the classification criteria are not met.
<u>Skin sensitization</u>	
Skin sensitization	May cause skin sensitization or allergic reactions in sensitive individuals.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	May cause cancer.
IARC carcinogenicity	Contains a substance which may be potentially carcinogenic. IARC Group 2B Possibly carcinogenic to humans.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	STOT RE 1 - H372 Causes damage to organs through prolonged or repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
General information	May cause cancer after repeated exposure. Risk of cancer depends on duration and level of exposure. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms known.
Ingestion	May cause sensitization or allergic reactions in sensitive individuals. May cause irritation.
Skin Contact	May cause skin sensitization or allergic reactions in sensitive individuals. Redness. Irritating to skin.
Eye contact	Irritating to eyes.
Route of entry	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.
Medical considerations	Skin disorders and allergies.

12. Ecological Information

Toxicity

Toxicity	Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.
-----------------	---

Persistence and degradability

Persistence and degradability	The degradability of the product is not known.
--------------------------------------	--

Bioaccumulative potential

Bio-Accumulative Potential	No data available on bioaccumulation.
-----------------------------------	---------------------------------------

Partition coefficient	Not available.
------------------------------	----------------

Rainshield Flat White Pastel

Mobility in soil

Mobility No data available.

Results of PBT and vPvB assessment

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

14. Transport information

Road transport notes This product is not regulated for transport by Department of Transportation (DOT)

UN Number

UN No. (DOT) Not applicable.

UN proper shipping name

Proper shipping name (DOT) Not applicable.

Transport hazard class(es)

DOT transport labels

No transport warning sign required.

Packing group

DOT packing group Not applicable.

Environmental hazards

Special precautions for user

DOT reportable quantity Not applicable.

DOT TIH Zone Not applicable.

15. Regulatory information

International Regulations

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed or exempt:

Silicon dioxide

Known to the State of California to cause cancer.

Rainshield Flat White Pastel

diuron

Known to the State of California to cause cancer.

Titanium dioxide

Known to the State of California to cause cancer.

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Zirconium(IV) oxide

Present.

Silicon dioxide

Present.

diuron

Present.

Limestone

Present.

t-Butyl hydroperoxide

Present.

Titanium dioxide

Present.

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

diuron

Present.

Limestone

Present.

t-Butyl hydroperoxide

Present.

Titanium dioxide

Present.

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

Silicon dioxide

Present.

diuron

Present.

Limestone

Present.

Titanium dioxide

Present.

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

diuron

Present.

Limestone

Present.

Rainshield Flat White Pastel

t-Butyl hydroperoxide

Present.

Titanium dioxide

Present.

3-iodo-2-propynyl butylcarbamate

Present.

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Silicon dioxide

Present.

diuron

Present.

Limestone

Present.

t-Butyl hydroperoxide

Present.

Titanium dioxide

Present.

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

16. Other information

Training advice Only trained personnel should use this material.

Revision comments Updated to meet OSHA updated GHS Standard.

Issued by Milton Arnold

Revision date 7/20/2016

Revision 2

SDS No. 4716

SDS status Approved.

Hazard statements in full H351 Suspected of causing cancer.
H401 Toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

End of SDS XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

